






Specialty Tags

CATALOG COMPARISON GUIDE

		 ■ GLOBAL	 ■ GLOBAL	 ■ GLOBAL	 ■ GLOBAL	HIGH MEMORY  ■ GLOBAL
Product Name		Adept 400	Adept 400	Adept 500	Adept 850	Adept 360°
Typical Applications		Piping Valves Processing Equipment	Piping Valves Processing Equipment	Gas Cylinders Beverage Kegs	Manufacturing & Supply Chain Automotive Outdoor & Industrial Operations	Very heavy industry applications. Identification of lifting equipment for maintenance and inventory management.
RF Specifications	Frequency Range (MHz)	860-930 (GS)	902-928 (US only)	860-930 (GS)	860-960 (GS)	860-930MHz (GS) 13.56MHz (HF opt)
	Read Range (m) Fixed reader Handheld reader	Up to 2.25 = 5 layer, Up to 4.0 = 4 layer Up to 1.35 = 5 layer, Up to 2.0 = 4 layer	Up to 4.5 Up to 1.8	Up to 5.0 Up to 5.0	Up to 8.5 Read, Up to 4 Write	Up to 10 (UHF), Up to 0.1 (HF opt) Up to 5.0 (UHF), Up to 0.1 (HF opt)
	Material Compatibility	Optimized for Metal	Optimized for Metal	Optimized for Metal	Optimized for Metal	Metal and non-metallic substrates
	IC Type	Monza 4QT	Alien Higgs 3	Alien Higgs 3	Qstar-5A	Alien H3 (UHF) NXP I-Code (HF opt.)
Physical and Environmental Specifications	Encasement	Stainless Steel with Ceramic Core	Stainless Steel with ceramic core	Durable Thermoplastic	ABS	Steel frame
	Size (mm)	45.0 x 30.5 x 15.5 = 5 layer 39 x 30.5 x 11.2 = 4 layer	36.0 x 25.0 x 13.5 = 5 layer 30 x 25 x 8.2 = 4 layer	37.0 x 37.0 x 11.5	65.0 x 45.0 x 8.0	137 x 48.0 x 5.50
	Weight (g)	94.0 = 5 layer, 53.0 = 4 layer	58.0 = 5 Layer, 35.0 = 4 layer	12.5	29.0	126
	Operating Temperature (°C)	-20 to +65	-20 to +65	-20 to +65	-20 to +85	-40 to +85
	Ingress Protection	IP68	IP68	IP68	IP68	IP68
	Shock and Vibration ¹	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G	MIL STD 810-G
	Attachment	Steel strap or welded = 5 layer Epoxy ² or welded = 4 layer	Steel strapping or welded = 5 layer Epoxy ² or welded = 4 layer	Premium foam (option)	Rivet/screw (not included) Foam or thin film Adhesive (option)	Tether attachment (not included)
Order Codes [†]	115 – GS For 4 layer, add option code :523	080 – (US only) For 4 layer, add option code :523	045 – GS	114 – GS	032 – GS	

¹ Products tested by third party in line with use case requirements.

² Customer to validate their epoxy.

[†] Order Option Codes are listed on the datasheets.

Specialty Tags

CATALOG COMPARISON GUIDE

Product Name					 GLOBAL
Typical Applications		Tool tracking Plastic handles on tools Surface mounting to plastic components of high value assets	Tracking returnable transit items Warehouse storage locations Rail carriage identification	Road Toll Collection Vehicle Access Control Vehicle Permits	Enterprise IT data center asset management
RF Specifications	Frequency Range (MHz)	902-928 (US) 866-868 (EU)	902-928 (US) 866-868 (EU)	902-928 (US) 866-868 (EU)	860-930 (GS)
	Read Range (m) – Fixed reader Handheld reader	Up to 3.5 Up to 1.75	Up to 12.0 (US), Up to 10.0 (EU) Up to 6.0 (US), Up to 5.0 (EU)	Up to 12.0 Up to 12.0	Up to 1.8 Up to 0.9
	Material Compatibility	Non-metallic substrates only	Metal and non-metallic substrates	Optimized	Metal & non-metallic substrates
	IC Type	Alien Higgs 3	Alien Higgs 3	Alien Higgs 3	Alien Higgs 3
Physical and Environmental Specifications	Material	Ceramic - Painted Black	ABS or Polycarbonate	Polypropylene structure and synthetic label	Synthetic Label
	Size (mm)	17.6 x 7.10 x 4.10	104 x 33.0 x 8.40	79.0 x 74.0 x 20.0	37.5 x 12.5 x 4.5
	Weight (g)	2.10	22.0	44.0	2.2
	Operating Temperature (°C)	-20 to +85	ABS: -40 to +55 Polycarbonate: -40 to +85	-40 to +65	-5 to +55°C
	Ingress Protection	IP68	IP68	IP65	IP54
	Shock and Vibration	MIL STD 810-G	MIL STD 810	MIL STD 810-G	MIL STD 810-G
	Attachment	Film adhesive (included)	Manual (std) Premium Foam adhesive (option)	Strap- not included	Film adhesive & tether hole (std) Premium foam adhesive (option)
Order Codes [†]	052 - US, EU	020 - US, EU	030 - US, EU	031 - GS	

[†] Order Option Codes are listed on the datasheets.

Need a Custom Tag?

We do that too.

www.omni-id.com/custom

